



Specification Sheet

Equipment Safety Systems Specification Sheet

Model Telehandler Safety System **eqss™** TSS 6245

General

Resolution Accuracy	
- Load	10K
- Length	10mm
- Angle	0.1°
Data Storage	Compact Flash Memory Card 512MB
Wind Speed Display Units	m/s, ft/s, km/h, knots

Housing

Case	UV Stabilised ABS Plastic
- Dimensions	164 (H) x 186(W) x 65(D) mm
Screen	Analogue Matrix LCD Screen
- Size	5.88" (119 x 80mm)
- Resolution	320 x 240 pixels
- Glass Material	Indium Tin Oxide (ITO) with Antiglare Hard Coat
Face Plate	Polycarbonate Fade Resistant Sticker
Rear Connector	Automotive IP68 (6 Pin)
LED Indicators	High Intensity Light Emitting Diodes
Weight	3 Kg (approx.)
Mounting Method	2xM6 Screw Bolt

Environment

Operating Temperature	-20°C Max
IP Rating	IP65
Humidity	20% to 95% RH (Relative Humidity)

Electrical

Power Supply	12VDC	24VDC
- Minimum	10.8	21.9
- Maximum	13.8	25.9
- Average Operating Current	600mA (Max 700mA)	300mA (Max 400mA)

EMC Compliance

N23041 Tested to: AS/NZS CISPR 22:2006

