



REV 1.1

07/06/2023

OverWatch Pre-Hire Inspection Checklist

DO001552

OVERWATCH PRE-HIRE INSPECTION CHECKLIST

It is recommended to complete an inspection of the EQSS OverWatch system as part of the MEWP pre-hire inspection. The goal is to confirm the OverWatch is functioning correctly and is undamaged. This inspection is to be carried out by a competent technician who has the expertise and experience to safely operate the MEWP and evaluate the operation and condition of the OverWatch.

Item	Action	Notes	Pass / Fail
Function assessment			
1.1	Indicator Light Confirm the light is visible when the OverWatch is active.	Light indicator is explained in the operator manual. Goto www.eqss.com.au/overwatchmanuals	
1.2	Audio – Elevate & Drive Confirm that the audio can be heard for “Elevate” and “Drive”	Stand in position select the mode of operation and press the joystick trigger	
1.3	Operator zone Stand out of the operator zone and press joystick trigger. System announces “Operator Zone”	Stand to the side of the control box or duck down, moving outside of the sensor zone. Press the joystick trigger.	
1.4	Sensor obstruction Hold hand over the face of the sensor and press the joystick trigger. System announces “Sensor Obstruction”	If sensor obstruction does not sound, check software version and update if necessary. Goto www.eqss.com.au/overwatchsoftware	
Visual inspection of Hardware			
2.1	Check operator sensor is attached and not loose.	The sensor should be fixed to the control box and secured correctly.	
2.2	Wiring is secure and not damaged	Wires should not be loose, check the wire from the operator sensor running into the control box	
2.3	Check operator sensor is clean.	Free of contamination, water, concrete paint. Remove and replace clear lens protector if necessary.	

Company:	Inspected by:
Date:	Signature: